

## **AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

1. (Currently Amended) An installation for intermediate storage of flat articles, the installation comprising:
  - a plurality of primary transport paths;
  - at least one secondary transport path;
  - a plurality of stations (1) for establishing and dissolving storage formations of the articles, said stations having entrances located at ends of a plurality of the primary transport paths, wherein the storage formations are imbricated formations of flat articles wound onto roll cores (11) and wherein the stations (1) are winding stations;
  - a plurality of passively displaceable mobile supporting elements (2) constructed to support one storage formation each and to be inserted into and retracted from the stations through the entrances, wherein the supporting elements (2) are roll stands with roll cores (11) rotatably installed thereon;
  - a plurality of storage spaces (2.1, 2.2) for storing the supporting elements (2), the storage ~~places~~ spaces being located on a plurality of the primary transport paths;
  - at least one positioning device, able to actively travel along the plurality of primary transport paths, for positioning and retrieving supporting elements (2) and

for transporting the supporting elements (2) along the primary paths, the at least one positioning device being movable forward and backward, wherein the at least one positioning device (5) is movable forward with one of the supporting elements on its front side, relative to a direction of travel, and is movable backward with one of the supporting elements on its back side, relative to the direction of travel; and

at least one orienting device (6, 6') for transporting the at least one positioning device along the at least one secondary transport path (4) and for changing an orientation thereof;

wherein at least part of the primary transport paths cross the at least one secondary transport path, wherein the at least one positioning device is adapted for positioning, retrieving, and transporting the supporting elements along the primary transport paths separated from the at least one orienting device, and wherein the at least one positioning device is adapted to be loaded to the at least one orienting device for orienting and transporting the supporting elements along the at least one secondary transport path.

2. (Previously Presented) The installation according to claim 1, wherein the primary transport paths (3) run parallel to one another and transverse to the at least one secondary transport path (4).
3. (Previously Presented) The installation according to claim 1, wherein the at least one positioning device (5) is an elevating truck (20) with a forklift (21).
4. (Previously Presented) The installation according to claim 1, wherein the at

least one positioning device (5) is displaceable along guide means.

5. (Previously Presented) The installation according to claim 4, wherein the guide means are rails or electrical guide lines.

6. (Previously Presented) The installation according to claim 1, wherein the at least one orienting device (6, 6') comprises means for holding the positioning device (5) and means for rotating the positioning device (5) around a vertical rotation axis (B).

7. (Previously Presented) The installation according to claim 6, wherein the means for rotating around a vertical axis (B) comprise a rotatable supporting frame (32) suspended from a supporting beam (30).

8. (Previously Presented) The installation according to claim 7, wherein the vertical axis (B) passes through the area of the center of gravity of the positioning device (5) being carried by the orienting device (6) and being loaded with a supporting element (2) with a storage formation.

9. (Previously Presented) The installation according to claim 6, wherein the at least one orienting device (6, 6') is adapted to simultaneously reorient and transport the one positioning device (5.1) together with a further positioning device (5.2).

10. (Previously Presented) The installation according to claim 9, wherein the

vertical axis (B) is positioned between the two positioning devices (5.1, 5.2) carried by the orienting device (6').

11. (Previously Presented) The installation according to claim 6, wherein the means for holding comprises a supporting frame (32) and a running substratum (33) arranged in the lower zone of the supporting frame (32), wherein the running substratum (33) is designed in such a manner, that the positioning device (5) is displaceable on it.

12. (Previously Presented) The installation according to claim 6, wherein the at least one orienting device (6, 6') additionally comprises means for elevating or lowering the positioning device (5).

13. (Previously Presented) The installation according to claim 12, wherein the means for elevating or lowering comprises a plurality of chain hoists (40), which are synchronously driven and coupled with the supporting beam (30).

14. (Previously Presented) The installation according to claim 1, wherein the orienting device (6, 6') is movable along a pair of rails (31).

15. (Previously Presented) The installation according to claim 1, wherein the installation further comprises at least one tertiary partial device (10) for transporting orienting devices (6, 6') along tertiary transport paths.

16. (Previously Presented) The installation according to claim 15, wherein the at least one tertiary partial device (10) is an elevator.

17. (Previously Presented) The installation according to claim 1, wherein the stations (1) for establishing or dissolving storage formations are arranged in the area of a first secondary transport path (4.1) and that at least one further, secondary transport path (4.2), parallel to the first secondary transport path (4.1), is provided.

Claim 18 (Cancelled)

Claim 19 (Cancelled)

Claim 20 (Cancelled)